

# TTP111HDLE

---

## Features

- ◆ Compatible with all HD-CVI, HD-TVI, HD-AHD
- ◆ Up to 450m for 720P CVI Cameras
- ◆ Up to 250m for 1080P CVI Cameras
- ◆ Up to 150m for 4MP CVI Cameras.
- ◆ Up to 250m for 720P/1080P/3MP TVI Cameras
- ◆ Up to 190m for 4MP TVI Cameras.
- ◆ Up to 320m for 720P AHD cameras
- ◆ Up to 250m for 1080P/4MP/5MP AHD cameras
- ◆ NTSC, PAL, and SECAM video formats
- ◆ No power required
- ◆ 60dB cross talk and noise immunity.
- ◆ Compact size and easy installation
- ◆ Press-fit terminal blocks
- ◆ With Lighting protector

## Technical Specifications

- ◆ Frequency response: DC to 60Mhz
- ◆ Attenuation: 0.5dB type
- ◆ CMRR: 60dB
- ◆ Connectors: Male BNC and "Press-Fit"
- ◆ Impedance: BNC: 75 ohms  
Terminal: 100 ohms
- ◆ Working Temperature: -10°C to +70°C
- ◆ Storage Temperature: -30°C to + 70°C
- ◆ Humidity : 0 to 95%
- ◆ Dimension: 39mm \* 16mm \* 19mm (excluding connectors)
- ◆ Material: ABS Plastic

## Application diagram

### Application : Passive-Passive UTP HD-CVI/TVI/AHD Transmission

